



ARCTIKO

The art of simplicity®

LOW TEMP. CHEST FREEZERS, -60°C

ULTRA LOW FREEZERS - LABORATORY, PHARMACEUTICAL AND MEDICAL REFRIGERATION

COST OF OWNERSHIP

It is a simple thing to make a cost of ownership analysis, and the Arctiko sales team is ready to provide you with the tool for this.

Taking into consideration that:

1 You save **40-50% energy** by using our patented single compressor system

2 You save **a similar percentage** on your air-conditioning due to the lower heat dissipation

3 You have the easiest and **less expensive service and maintenance without comparison**

It is a fact that within a couple of years, the buying price of the freezer is saved in energy cost. And at the same time, you are more environmentally friendly!


Please ask your local dealer for help or contact the Arctiko team for more information.



Net capacity
71 L

LTF 85

Temperature	-60°C
Net capacity	71 L
40 pcs. 50 mm boxes	



Net capacity
133 L

LTF 225

Temperature	-60°C
Net capacity	133 L
117 pcs. 50 mm boxes	



Controller features

- Digital display
- Visual and acoustic alarm
- Adjustable high/low temperature alarm
- Contact for remote alarm
- Probe failure alarm

LTF RANGE

Low temperature freezer


As a synonym for security, the LTF and LTFE range ensure reliable low temperature freezing and high temperature uniformity. Digital display, alarms, contact for remote alarm and castors are some of the standard features.



Net capacity
284 L

LTF 325


Temperature **-60°C**
Net capacity **284 L**
216 pcs. 50 mm boxes



Net capacity
368 L

LTF 425


Temperature **-60°C**
Net capacity **368 L**
282 pcs. 50 mm boxes



Net capacity
476 L

LTF 535

Temperature **-60°C**
Net capacity **476 L**
345 pcs. 50 mm boxes



www.arctiko.com



LTF RANGE

Model	LTF 85	LTF 225	LTF 325	LTF 425	LTF 535
Dimensions exterior WxDxH (mm)	552x648x850	722x698x885	1262x698x885	1562x698x885	1662x758x890
Capacity (L)	71	133	284	368	476
Dimensions interior WxDxH (mm)	390x390x465	560x440x635	1100x440x635	1400x440x635	1500x500x675
Temperature range (°C)	-60 / -30	-60 / -30	-60 / -30	-60 / -30	-60 / -30
Power supply (V) / Frequency (Hz)	230 - 50/60	230 - 50/60	230 - 50/60	230 - 50/60	230 - 50/60
No. of compressors	1	1	1	1	1
Visual / Acoustic alarm	Yes	Yes	Yes	Yes	Yes
Adjustable high/low temperature alarm	Yes	Yes	Yes	Yes	Yes
Probe failure alarm	Yes	Yes	Yes	Yes	Yes
Contact for remote alarm	Yes	Yes	Yes	Yes	Yes
Prepared for GSM alarm module	Yes	Yes	Yes	Yes	Yes
Porthole for installation of PT100/CO ₂ back up	Yes	Yes	Yes	Yes	Yes
Digital display	Yes	Yes	Yes	Yes	Yes
Defrost manual / auto	Manual	Manual	Manual	Manual	Manual
Castors	No	Yes	Yes	Yes	No
Lighting	No	No	No	No	No
Lock	Yes	Yes	Yes	Yes	Yes
Inner liner material	Varnished steel	Varnished steel	Varnished steel	Varnished steel	Varnished steel
Cabinet material	Varnished steel	Varnished steel	Varnished steel	Varnished steel	Varnished steel

* Optional, please contact us
We reserve the right to change specifications without notice and subject to errors.



ARCTIKO
The art of simplicity®



www.arctiko.com

